


INNOVA

by etex

Product brochure

June 2026

Fibre cement specialists.



Backed by Etex, the global leader in fibre cement, Innova is bringing the change the industry needs. So now architects, builders, and homeowners can make the changes they want.

We'll never stop innovating our stylish fibre cement range. We'll never stop finding efficiencies and passing on the savings.

Change is what defines us and propels us forward. Change is the foundation we're built on.

Innova. Built on change.



Nuline®
Square
175mm

INOVA

by etex

Innova is Australia's top supplier of facades and linings, committed to bringing design, quality and value to domestic and commercial projects of all sizes.

Inside and out, we offer traditional and contemporary styling, with a wide variety of designs, created to inspire and impress. You'll also enjoy the peace of mind of a smooth building process with products that are versatile, durable and will stand the test of time.

This is form and function.

This is art and innovation.

This is Innova.

The range you've been waiting for.

Exterior and interior walls

Weatherboards	3
Nuline®	4
Stratum®	7
Contour®	10
Duraplank®	13
Exterior facades	17
Duragroove®	18
Durascape®	21
Duragrid®	24
Duracom®	27
Exterior base sheets	29
Duratex®	30
Stonesheet®	32
Pre-finished facades	35
Montage®	36
Pre-cladding	45
DurabARRIER®	46
Interior linings	49
Duraliner®	50
Intergroove®	52
Innova on the inside	54

Eaves and soffits

Eaves lining and soffits	57
Durasheet®	58
Duralux®	60

Flooring and underlay

Flooring	63
Durafloor®	64
Compressed flooring	66
Underlay	69
Ceramic tile underlay	70

Effects

Effects® trims	74
Effects® fascia	75
Effects® base trim	76

Warranty

Please refer to innovafibreceement.com.au for detailed warranty information.

Disclaimer

Innova regularly updates its literature; to ensure this document is current with the latest information, visit innovafibreceement.com.au

Nuline®
Square
175mm



Exterior and interior walls

Weatherboards

Nuline®

Weatherboards

Nuline® is a sleek, weatherboard cladding system designed to deliver a modern and sophisticated aesthetic. It offers the timeless charm of traditional weatherboards without the ongoing maintenance associated with timber.

Thanks to its innovative tongue-and-groove design, Nuline® ensures perfectly consistent joins across your project. Additionally, the slight bevel on the rear of each plank provides a 25mm bearing face on the stud, making fixing and nailing both straightforward and efficient.




Features and benefits


- Extend your options with 2 different profiles: square & bullnose.
- Delivered primed and ready for painting, saving preparation time.
- Built for longevity with high durability and resistance to rot and decay.
- Quick, simple installation: manual nailing, gun nailing or screw fixing.
- Complies with BAL-40 as required in AS 3959 — Construction of buildings in bushfire-prone areas.

Thickness mm	Profile	Weight kg/lm	Width mm	Length mm	Product code	Pack size
14	Square	3.4	175	4200	4092767	120
	Square	4	205		4092768	120
	Bullnose	3.4	175		4092762	120
	Bullnose	4	205		4092763	120

Profiles



Square



Bullnose





No. of weatherboards	4200 x 175	4200 x 205
	Weatherboard overlap 30mm	Weatherboard overlap 30mm
	Effective cover per weatherboard 4200 x 145mm or 0.609m ²	Effective cover per weatherboard 4200 x 175mm or 0.736m ²
1	175	205
2	320	380
3	465	555
4	610	730
5	755	905
6	900	1080
7	1045	1255
8	1190	1430
9	1335	1605
10	1480	1780
11	1625	1955
12	1770	2130
13	1915	2305
14	2060	2479
15	2205	2655
16	2350	2830
17	2495	3005
18	2640	3180
19	2785	3355
20	2930	3530



Product: Nuline® Square 205mm

Accessories



36mm Aluminium internal corner

Size mm	Product code
3000 × 36	4092823



36mm Aluminium external corner

Size mm	Product code
3000 × 36	4092819




Nuline® 175mm external corner soaker (25pcs)

Size mm	Product code
175	4094306




Nuline® 205mm external corner soaker (25pcs)

Size mm	Product code
205	4094307



J mould

Size mm	Product code
2700 × 14	4092811




PVC Nuline starter strip

Size mm	Product code
3000 × 13	4093794



PVC Cavity Closer

Size mm	Product code
3000 × 35	4094331



Thermal break (reduces thermal bridging when installing on steel frame)

Size mm	Product code
12500 × 8	4092824



Sikaflex® 11 FC+ sealant adhesive

Weight g	Product code
300	4094941

Product: Nuline® Square 175mm



Stratum®

Weatherboards

A vibrant, innovative alternative to traditional weatherboards, Stratum® is an endlessly adaptable range of weatherboard products. Choose one Stratum® profile as a standalone, or mix'n'match two or three to create eye-catching and original exterior cladding.

Stratum® is designed with a shiplap join, meaning installation is quicker and easier and the smooth profiles come pre-primed to speed up the painting process.

5 unique profiles make up the Stratum® range

- Stratum® is a 300mm wide weatherboard.
- Stratum® Woodgrain is a 300mm wide weatherboard embossed with a woodgrain pattern giving a timber like appearance.
- Stratum® Duo is a 300mm wide weatherboard with a 16mm centre groove giving the look of two slimmer weatherboards.
- Stratum® Duo Woodgrain is a 300mm wide weatherboard with a 16mm centre groove giving the look of two slimmer weatherboards embossed with a woodgrain pattern giving a timber like appearance.
- Stratum® Trio is a 300mm wide weatherboard with 2 x 16mm horizontal grooves.

Features and benefits


- Features easy shiplap joining for a seamless finish.
- Smooth profiles are primed and ready for painting, saving preparation time.
- Quick, simple installation: manual nailing, gun nailing or screw fixing.
- Complies with BAL-40 as required in AS 3959 — Construction of buildings in bushfire-prone areas.



Thickness mm	Profile	Weight kg/lm	Width mm	Length mm	Product code	Pack size
12	Stratum®	5	300	4200	4092780	90
	Stratum® Woodgrain	5			4092787	90
	Stratum® Duo	4.3			4092775	90
	Stratum® Duo Woodgrain	4.3			4092777	90
	Stratum® Trio	4.2			4092783	90




Profiles



Stratum®



Stratum® Duo



Stratum® Trio



Stratum® Woodgrain



Stratum® Duo Woodgrain

	4200 × 300
	Weatherboard overlap 24mm
No. of weatherboards	Effective cover per weatherboard 4200 × 276mm or 1.159m²
1	300
2	576
3	852
4	1128
5	1404
6	1680
7	1956
8	2232
9	2508
10	2784
11	3060
12	3336
13	3612
14	3888
15	4164
16	4440
17	4716
18	4992
19	5268
20	5544



Accessories



Aluminium internal corner

Size mm	Product code
3000 × 17	4092822



Aluminium external corner

Size mm	Product code
3000 × 17	4092818



Aluminium external corner snap on corner part B

Size mm	Product code
3600	4092918



Aluminium external corner snap on corner Part C

Size mm	Product code
3600	4092919




Stratum® joiner (for use joining Stratum planks at a continuous vertical joints and control joints)

Size mm	Product code
3000	4092920



PVC Cavity Closer

Size mm	Product code
3000 × 35	4094331



Thermal break (reduces thermal bridging when installing on steel frame)

Size mm	Product code
12500 × 8	4092824



Primary EPDM foam gasket (weatherproofing protection at vertical joints when planks are staggered)

Size mm	Product code
25000 × 48 × 3	4092813



Sikaflex® 11 FC+ sealant adhesive

Size g	Product code
300	4094941

Product: Stratum® and Duragrid®



Contour[®]

Weatherboards

The Contour[®] board is expertly designed to replicate the charm of older-style weatherboard homes, featuring a rebate at the top of each plank to enhance the shadowline for a more defined, traditional appearance. It combines the classic appeal of weatherboards with the modern advantage of low-maintenance durability.

With its narrower profile and distinctive rebate, the Contour[®] board delivers a truly authentic weatherboard look, setting it apart from other cladding options.

Features and benefits

- Narrower profile for a traditional weatherboard aesthetic.
- Delivered primed and ready for painting, saving preparation time.
- Built to last with exceptional durability, resistant to rot and decay.

- Quick, simple installation: manual nailing, gun nailing or screw fixing.
- Complies with BAL-40 as required in AS 3959 — Construction of buildings in bushfire-prone areas.
- Concealed fixing for a seamless finish.



Thickness mm	Weight kg/lm	Width mm	Length mm	Product code	Pack size
10	2.4	170	4200	4092772	180

Profile



Contour[®]





No. of weatherboards	4200 x 170
	Weatherboard overlap 24mm
Effective cover per weatherboard 4200 x 141mm or 0.592m ²	
1	170
2	311
3	452
4	593
5	734
6	875
7	1016
8	1157
9	1298
10	1439
11	1580
12	1721
13	1862
14	2003
15	2144
16	2285
17	2426
18	2567
19	2708
20	2849



Accessories



Aluminium internal corner

Size mm	Product code
3000 × 25	4092916



Aluminium external corner

Size mm	Product code
3000 × 25	4092914



Aluminium external corner snap on corner part A

Size mm	Product code
3600	4092917




Aluminium external corner snap on corner Part B

Size mm	Product code
3600	4092918




PVC Cavity Closer

Size mm	Product code
3000 × 35	4094331




Powdercoated steel starter strip

Size mm	Product code
3000	4092882



Primary EPDM foam gasket (secondary weatherproofing protection at sheet joins)

Size mm	Product code
25000 × 48 × 3	4092813



Thermal break (reduces thermal bridging when installing on steel frame)

Size mm	Product code
12500 × 8	4092824



Sikaflex® 11 FC+ sealant adhesive

Size g	Product code
300	4094941

Duraplank®

Weatherboards

Duraplank® combines the timeless appeal of traditional weatherboards with modern durability and ease of installation. Designed to resist decay, rot, and termite damage, this non-combustible cladding solution is built to last.

With two attractive finish options – smooth and woodgrain — Duraplank® delivers an authentic weatherboard aesthetic while offering the strength to endure the demands of everyday life.

Features and benefits

- Evokes the charm of traditional weatherboards.
- Built for longevity with high durability and resistance to rot and decay.
- Quick, simple installation: manual nailing, gun nailing or screw fixing.
- Complies with BAL-29 as required in AS 3959 — Construction of buildings in bushfire prone areas.

Thickness mm	Profile	Weight kg/lm	Width mm	Length mm	Product code	Pack size
7.5	Smooth	2.4	230	4200	4092793	120
	Smooth	3.1	300		4092794	120
	Woodgrain	2.4	230		4092796	120
	Woodgrain	3.1	300		4092797	120

Profiles



Smooth



Woodgrain





	4200 x 230	4200 x 300
	Weatherboard overlap 25mm	Weatherboard overlap 25mm
No. of weatherboards	Effective cover per weatherboard 4200 x 205mm or 0.861m ²	Effective cover per weatherboard 4200 x 275mm or 1.155m ²
1	230	300
2	435	575
3	640	850
4	845	1125
5	1050	1400
6	1255	1675
7	1460	1950
8	1665	2225
9	1870	2500
10	2075	2775
11	2280	3050
12	2485	3325
13	2690	3600
14	2895	3875
15	3100	4250
16	3305	4525
17	3510	4800
18	3715	5075
19	3920	5350
20	4125	5625

Accessories



PVC joiner smooth

Size mm	Product code
230	4092808
300	4092874



PVC joiner woodgrain

Size mm	Product code
230	4092875
300	4092876



Aluminium internal corner

Size mm	Product code
3000 × 25	4092916



Aluminium external corner

Size mm	Product code
3000 × 25	4092914



Aluminium external corner snap on corner part A

Size mm	Product code
3600	4092917



Aluminium external corner snap on corner Part B

Size mm	Product code
3600	4092918




PVC Cavity Closer

Size mm	Product code
3000 × 35	4094331




Off stud joiner (25pcs)

Size mm	Product code
230	4094308
300	4094310



PVC Duraplank starter strip

Size mm	Product code
3000 × 8.5mm	4094330



Thermal break (reduces thermal bridging when installing on steel frame)

Size mm	Product code
12500 × 8	4092824



Duraplank® internal corner soaker (25pcs)

Size mm	Product code
230	4094302
300	4094304



Duraplank® external corner soaker (25pcs)

Size mm	Product code
230	4094303
300	4094305



Sikaflex® 11 FC+ sealant adhesive

Size g	Product code
300	4094941



Duraplank®
Smooth

Exterior and interior walls

Exterior facades

Duragroove®

Exterior facades

Duragroove® is a highly versatile, vertically grooved panel designed to add striking visual appeal to any project. Its sleek, modern design enhances contemporary spaces, and the option to mix and match profiles allows for endless creative expression.

Produced in large sheets across a variety of sizes, Duragroove® features a shiplap join for a seamless appearance and quicker installation. With four unique profiles, it's easy to achieve the perfect look:

- **Narrow:** 100mm between grooves.
- **Wide:** 150mm between grooves, with an enhanced groove width for added visual appeal.
- **Extra Wide:** 400mm between grooves, with an enhanced groove width for added visual appeal.
- **Wide Woodgrain:** 150mm between grooves, featuring a natural woodgrain texture and an enhanced groove width.



Features and benefits

- Excellent choice for long wall spans, offering large panel sizes that cover more square meters per sheet.
- It's efficient design reduces installation time while delivering a clean, modern finish.
- Acrylic-sealed panels improve paint adhesion and finish.
- Quick to install — no need for taped and filled joints.
- Panels resistant to termites, air, steam, salt and sunlight.
- Complies with BAL-40 as required in AS 3959 — Construction of buildings in bushfire-prone areas.

Thickness mm	Weight kg/m ²	Profile	Width mm	Length and product code				Pack size
				2450mm	2750mm	3000mm	3600mm	
9	12.4	Smooth Narrow	1200	4092596	4092597	4092598		40
		Smooth Wide 5mm Groove		4092599	4092600	4092601	4092602	40
		Smooth Extra Wide		4092590	4092591	4092592		40
		Woodgrain 5mm Groove		4092603	4092604	4092605		40
9	12.4	Smooth Wide 10mm Groove	1200	4095539	4095542	4095543	4095544	40
		Woodgrain Wide 10mm Groove		4096402	4096403	4096404		40


Available
from May
Available
from June

Profiles





Narrow



Wide




Extra Wide



Woodgrain Wide



Wide 10mm Groove



Woodgrain Wide 10mm Groove



Accessories



Aluminium internal corner

Size mm	Product code
3000 × 12	4092821



Aluminium external corner

Size mm	Product code
3000 × 12	4092817



Horizontal H flashing

Size mm	Product code
3000	4092820



Aluminium external corner snap on corner part B

Size mm	Product code
3600	4092918




Aluminium external corner snap on corner Part C

Size mm	Product code
3600	4092919



PVC Cavity Closer

Size mm	Product code
3000 × 35	4094331



Thermal break (reduces thermal bridging when installing on steel frame)

Size mm	Product code
12500 × 8	4092824



Primary EPDM foam gasket (secondary weatherproofing protection at sheet joins)

Size mm	Product code
25000 × 48 × 3	4092813



Sikaflex®11 FC+ sealant adhesive

Size g	Product code
300	4094941

Product: Duragroove® Smooth Narrow



Durascape®

Exterior facades

Durascape® is the perfect solution for projects requiring a sleek, large panel aesthetic. It is a cladding solution featuring a 5mm shiplap joint that creates a subtle vertical shadowline while ensuring quick and easy installation. The shiplap design also minimizes movement, removing the risk of cracking over time.

For a bold, contemporary look, Durascape® delivers a sleek 'rendered' finish when coated with textured paint on-site—offering limitless design potential and a striking modern aesthetic.




Features and benefits

- Easy to handle and built to last.
- Perfect for single-story and medium-height applications with large panels.
- Quick installation — no need for taped and flushed joints.
- Panels unaffected by termites, air, steam, salt and sunlight.
- Can be finished in a range of decorative coatings.
- Complies with BAL-40 as required in AS 3959 — Construction of buildings in bushfire-prone areas.

Thickness mm	Weight kg/m ²	Width mm	Length mm	Product code	Pack size
9	12.4	900	2450	4092626	40
			3000	4092628	
		1200	2450	4092625	
			3000	4092627	

Profile



Durascape®





Accessories



Aluminium internal corner

Size mm	Product code
3000 × 12	4092821



Aluminium external corner

Size mm	Product code
3000 × 12	4092817



9mm Horizontal H flashing

Size mm	Product code
3000	4092820



Aluminium external corner snap
on corner part B

Size mm	Product code
3600	4092918




Aluminium external corner snap
on corner Part C

Size mm	Product code
3600	4092919




PVC Cavity Closer

Size mm	Product code
3000 × 35	4094331



Primary EPDM foam gasket
(secondary weatherproofing
protection at sheet joins)

Size mm	Product code
25000 × 48 × 3	4092813



Thermal break (reduces thermal
bridging when installing on steel frame)

Size mm	Product code
300	4094941



Sikaflex® 11 FC+ sealant adhesive

Size g	Product code
3000 × 35	4094331

Duragrid®

Exterior facades

Duragrid® is a cutting-edge cladding system featuring a sleek, geometric 10mm expressed join for a modern and stylish aesthetic. Ideal for projects aiming to achieve a clean and contemporary design. Duragrid® panels offer exceptional design flexibility.

Designed for versatility, Duragrid® can be installed on timber or lightweight steel battens, creating a cavity that enhances thermal properties and achieves higher R values. Duragrid® makes it easy to add a variety of stunning decorative finishes.



Features and benefits

- Built to withstand the elements while being easy to handle.
- Compatible with a range of coatings, from paint to textured finishes.
- Unaffected by termites, air, steam, salt or sunlight.
- Quick and simple hand nail, gun-nail or screw fixing options.
- Suitable for residential projects with timber battens or light commercial installations with steel battens.
- Ultimate layout flexibility with horizontal or vertical installation in a brick or stack bond layout to suit your projects design.
- Complies with BAL-40 as required in AS 3959 — Construction of buildings in bushfire-prone areas.

Thickness mm	Weight kg/m ²	Width mm	Length and product code				Pack size
			1190mm	1790mm	2390mm	2990mm	
9	12.4	590			4092588		40
		890		4092586			40
		1190	4092585			4092589	40

Profile



Duragrid®






Accessories



Durabatten timber ply H5 treated



Cladding top hat




PVC cavity closer

Size mm	Product code	Size mm	Product code	Size mm	Product code
2700 × 75 × 19	4092848	3000 × 70 × 19 0.75BMT	311584	2700 × 19	4092846
		3000 × 70 × 35 0.75BMT	311655	3000 × 35	4094331



Sikaflex® 11 FC+ sealant adhesive



Facade backing strip

Size g	Product code	Size mm	Product code
300	4094941	1190	298168
		2390	298169
		2990	298170



Duracom[®]

Exterior facades

Duracom[®] is the perfect solution for creating visually striking facades in all buildings. Designed with commercial projects in mind, Duracom[®] uses compressed fibre cement panels combined with a steel top hat system for exceptional durability and impact resistance.

The system's signature 10mm express join delivers a sophisticated grid-like pattern that can be customized into various shapes and sizes, allowing flexibility to suit any design vision. Duracom[®] supports a wide range of finishes, from sleek painted surfaces to textured coatings, ensuring a versatile and modern look.



Features and benefits

- Delivered primed and ready for painting, saving preparation time.
- Compatible with a variety of decorative finishes for unique facade styles.
- Quick and simple installation using top hats.
- Complies with BAL-40 as required in AS 3959 — Construction of buildings in bushfire-prone areas.
- Suitable for high wind zones applicable up to 7kPA.

Thickness mm	Weight kg/m ²	Width mm	Length and product code				Pack size
			1800mm	2400mm	2700mm	3000mm	
9	14.2	900	4092551	4092553		4092556	40
		1200	4092550	4092552	4092554	4092555	40
12	18.9	1200		4093682		4092546	30


Profile




Duracom[®]




Accessories



Primary top hat



Intermediate top hat




Facade backing strip

Size mm	Product code	Size mm	Product code	Size mm	Product code
6000 × 120 × 35 0.75BMT	311515	6000 × 50 × 35 0.75BMT	298296	1190	298168
6000 × 120 × 35 1.15BMT	298172	6000 × 50 × 35 1.15BMT	298299	2390	298169
				2990	298170



Sikaflex® 11 FC+ sealant adhesive



Primary EPDM foam gasket
(secondary weatherproofing
protection at sheet joins)



Weather seal washer

Size g	Product code	Size mm	Product code	Product code
300	4094941	25000 × 48 × 3	4092813	4092581

Product: Duracom®



Exterior and interior walls

Exterior base sheets

Duratex[®]

Exterior base sheets

Duratex[®] is a durable, non-combustible fibre cement sheet designed for both residential and commercial applications. It serves as a strong and stable cladding solution, providing a high-quality base for a variety of exterior finishes

Duratex[®] is designed to accept multiple coating options, including textured coatings, acrylic renders. Its robust construction ensures long-term performance, making it an excellent choice for modern building projects.

Features and benefits

- Non-combustible, providing added safety and durability.
- Suitable for both residential and commercial applications.
- Accepts a variety of finishes, using proprietary jointing and coating systems.
- Strong, long-lasting, and easy to install.
- Complies with AS3959 — Construction of buildings in bushfire-prone areas (7.5mm: BAL-29; 9.0mm: BAL-40).

Thickness mm	Weight kg/m ²	Width mm	Length and product code				Pack size
			2400mm	2440mm	2725mm	3000mm	
7.5	10.4	1200		4092630	4092631	4092632	50
9	12.4	1200	4092633			4092634	40





Stonesheet®

Exterior base sheets

Stonesheet® is the ideal choice for stone wall substrates and true masonry on timber or steel-framed buildings.

This 9mm thick, flat, square-edged panels are designed specifically for both residential interior and exterior applications, offering a reliable and purpose-built solution where other substrates may fall short.

Stonesheet® is the perfect base for stone tile facades, providing excellent performance and durability.

Features and benefits

- Suitable for both exterior and interior stone tile facades.
- Classified Type A Category 3 for exterior use ensuring reliability.
- Non-structural substrate.
- Capable of supporting a maximum stone facade weight of 40kg/m².
- Complies with BAL-40 as required in AS 3959 — Construction of buildings in bushfire prone areas.

Thickness mm	Weight kg/m ²	Width mm	Length mm	Product code	Pack size
9	12.4	1200	3000	4092629	40





*This product is a substrate only and does not include stones.



Montage®
Woodgrain
Black Oak

Montage®
Concrete
Rectangle
with Circle

Montage®
Woodgrain
Light Teak

Montage®
Slimline Tile
Limestone

Exterior and interior walls

Pre-finished facades

Montage®

Pre-finished facades

Montage® is a versatile fibre cement facade system that can be used both externally and internally.

The range brings depth and texture to your project, offering the flexibility to combine profiles and colours for a truly unique and distinctive final look.


With a colour palette carefully considered to be blended or contrasted, you'll have an array of options to play with. The deep form embossed into the panels also creates a striking effect, making your project stand out from the streetscape.



Features and benefits

- 4 profiles available — Concrete, Slimline Tile, Stackstone and Woodgrain.
- Lightweight and easy to install.
- Perfect for internal or external installation.
- Pre-finished using a multiple coat finishing system.
- Fully sealed panels that are weather resistant and won't rot or burn.
- Complies with BAL-40 as required in AS 3959 — Construction of buildings in bushfire prone areas.
- Quick and Simple to install.
- Uses a concealed clip fixing system creating a seamless finish.

Thickness mm	Profile	Weight kg/m ²	Width mm	Length mm	Product code	Pack size
16	Concrete — Square with Circle	18.9	455	3030	4092705	1
	Concrete — Rectangle with Circle				4092704	1
	Concrete — Smooth Plain				4092706	1
18	Slimline Tile — Limestone	17			4092673	1
	Slimline Tile — Sandstone				4092674	1
	Slimline Tile — Basalt				4092675	1
	Slimline Tile — Onyx				4092676	1
18	Stackstone — Limestone	16.7			4092684	1
	Stackstone — Sandstone				4092681	1
	Stackstone — Basalt				4092682	1
	Stackstone — Onyx				4092683	1
18	Woodgrain — Light Teak	17.8			4092661	1
	Woodgrain — Dark Mahogany				4092662	1
	Woodgrain — Grey Oak				4092663	1
	Woodgrain — Black Oak				4092664	1



Woodgrain Light Teak, Woodgrain Black Oak, Concrete Rectangle Circle, Concrete Smooth plain are stock items.

All other profiles are made to order, please contact your local Innova representative for more details.



Profiles


Concrete



Square with Circle




Rectangle with Circle



Smooth Plain

Slimline Tile




Limestone



Sandstone



Basalt



Onyx

Stackstone



Basalt



Onyx




Sandstone




Limestone


Woodgrain




Light teak



Dark Mahogany



Grey Oak



Black Oak

Product: Montage® Concrete Rectangle with Circle, Montage® Stackstone Rectangle with Circle and Montage® Slimline Tile Limestone



Pre-formed corners — horizontal installation



Concrete



Woodgrain

Size mm	Product code	Profile	Size mm	Product code
455 × 16	4092742	Light Teak	455 × 18	4092669
		Dark Mahogany	455 × 18	4092670
		Grey Oak	455 × 18	4092671
		Black Oak	455 × 18	4092672



Slimline Tile



Stackstone

Profile	Size mm	Product code	Profile	Size mm	Product code
Limestone	455 × 18	4092677	Limestone	455 × 18	4092688
Sandstone	455 × 18	4092678	Sandstone	455 × 18	4092685
Basalt	455 × 18	4092679	Basalt	455 × 18	4092686
Onyx	455 × 18	4092680	Onyx	455 × 18	4092687

Pre-formed corners — vertical installation




Woodgrain


Profile	Size mm	Product code
Light Teak	3030 × 18	4092665
Dark Mahogany	3030 × 18	4092666
Grey Oak	3030 × 18	4092667
Black Oak	3030 × 18	4092668

Installation accessories — powder coated aluminium corners — common

Profile		Size mm	Product code
Aluminium external corner for Concrete and Woodgrain Grey Oak		3600 × 36	4092709
Aluminium external corner for Slimline Tile and Stackstone Limestone			4092711
Aluminium external corner for Slimline Tile and Stackstone Sandstone			4092714
Aluminium external corner for Slimline Tile and Stackstone Basalt			4092708
Aluminium external corner for Slimline Tile and Stackstone Onyx and Woodgrain Black Oak			4092713
Aluminium external corner for Woodgrain Light Teak			4092712
Aluminium external corner for Woodgrain Dark Mahogany			4092710
Aluminium internal corner for Concrete and Woodgrain Grey Oak			4092736
Aluminium internal corner for Slimline Tile and Stackstone Limestone			4092738
Aluminium internal corner for Slimline Tile and Stackstone Sandstone			4092741
Aluminium internal corner for Slimline Tile and Stackstone Basalt			4092735
Aluminium internal corner for Slimline Tile and Stackstone Onyx and Woodgrain Black Oak			4092740
Aluminium internal corner for Woodgrain Light Teak			4092739
Aluminium internal corner for Woodgrain Dark Mahogany			4092737



Installation accessories — vertical



Vertical cavity starter

Size mm	Product code
150	4092702



Cavity clip

Size mm	Product code
62 × 50 × 5	4092700



Self adhesive spacer

Size mm	Product code
50 × 50 × 5	4092698




High hat joiner

Size mm	Product code
3030 × 10	4092690



Single hat joiner

Size mm	Product code
3030 × 10	4092692



Top hat

Size mm	Product code
3000 × 75 × 15 1.15 tct	311656

Size mm	Product code	Size mm	Product code
3030 × 20	4092691	2000 × 16	4092693

Installation accessories — horizontal



Horizontal cavity starter

Size mm	Product code
3030	4092703




Cavity clip

Size mm	Product code
60 × 56 × 15	4092701



Self adhesive spacer

Size mm	Product code
50 × 50 × 15	4092699



High hat joiner


Size mm	Product code
3030 × 20	4092691



Single hat joiner

Size mm	Product code
2000 × 16	4092693

Installation accessories — common



Internal corner flashing

Size mm	Product code
3050 × 40 × 40	4092694



Ring nail for face fixing on timber

Size mm	Product code
65 × 3	4092695



Montage primer

Size ml	Product code
200	4094691



SS screws for clips to the frame

Size mm	Product code
35	4092696



SS screws for clips to steel frame

Size mm	Product code
19 × 4	4092697

Installation accessories — eaves



Eaves trim channel

Profile	Size mm	Product code
Grey	2370 × 55 × 35	4092724
Brown		4092726
Black		4092725



External corner

Profile	Size mm	Product code
Grey	86 × 32.5 × 51.3	4092727
Brown		4092729
Black		4092728




Internal corner

Profile	Size mm	Product code
Grey	86 × 67.4 × 32.5	4092730
Brown		4092732
Black		4092731



Trim joint


Profile	Size mm	Product code
Grey	40 × 32.5	4092721
Brown		4092723
Black		4092722





End cap

Profile	Size mm	Product code
Grey	32.5 × 25	4092718
Brown		4092720
Black		4092719

Accessories — sealants

Profile		Size ml	Product code
Concrete grey sealant for Concrete profiles, Stackstone Basalt and Woodgrain Grey Oak		600	4092825
			
Off white sealant for Slimline Tile and Stackstone Limestone			4092831
Sandstone sealant for Slimline Tile Sandstone			4092829
Dark Grey sealant for Slimline Tile Basalt and Stackstone Onyx			4092830
Black sealant with Slimline Tile Onyx and Woodgrain Black Oak			4092826
Redwood sealant for Stackstone Sandstone and Woodgrain Light Teak			4092827
			
Dark Amber for Woodgrain Dark Mahogany			4092828

Accessories — touch up paint

Profile		Size ml	Product code
Concrete		80	4092746
Woodgrain — Light Teak			4092758
Woodgrain — Dark Mahogany			4092756
Woodgrain — Grey Oak			4092757
Woodgrain — Black Oak			4092755
Slimline Tile — Limestone			4092752
Slimline Tile — Sandstone			4092754
Slimline Tile — Basalt			4092751
Slimline Tile — Onyx			4092753
Stackstone — Sandstone			4092750
Stackstone — Limestone			4092748
Stackstone — Basalt			4092747
Stackstone — Onyx			4092749



Durabarrier®

Exterior and interior walls

Pre-cladding

DurabARRIER®

Pre-cladding

DurabARRIER® is a rigid air barrier designed for both residential and commercial buildings with timber or steel framing. Made from fibre cement and finished with a water-repellent sealer, it's a tough, reliable alternative to traditional wall wraps or sarking.

DurabARRIER® is ideal for projects that need high performance and long-lasting protection from the elements. When used with a cladding system that includes a drained and ventilated cavity, it helps manage moisture effectively. This allows the building to breathe, reduces the chance of water getting in, and supports a healthier, drier indoor environment.

Features and benefits

- Guards against moisture damage, corrosion and rot with a tough, sealed fibre cement sheet.
- Class 4 permeability allows buildings to breathe whilst keeping moisture out.
- Withstands high wind pressures and offers 6 months of temporary weather protection prior to the cladding being installed.
- Enables internal work to begin before cladding goes on, saving time on site.
- Suitable for steel and timber frames, direct fix and cavity wall systems and is non combustible.

Thickness mm	Weight kg/m ²	Width mm	Length and product code		Pack size
			2450mm	3000mm	
6	8.3	1200	4092579	4092580	60







Duraliner®

Exterior and interior walls

Interior linings

Duraliner[®]

Interior linings

Duraliner[®] is a general-purpose fibre cement lining board, designed for flush jointing and ideal for a variety of applications. It excels in wet areas, interior linings, and as a substrate for ceramic wall tiles, as well as for fire and acoustically-rated interior walls.

Features and benefits

- Ideal for use in fire and acoustic-rated wall applications.
- Suitable for a wide range of uses, including internal wet areas.
- Rebated on 3 edges for efficient jointing and installation.

Thickness mm	Weight kg/m ²	Width mm	Length and product code						Pack size
			1800mm	2400mm	2700mm	3000mm	3600mm	4200mm	
6	8.3	900		4092610					60
		1200	4092607	4092608	4092611	4092612	4092615		60
								4092617	50
		1350		4092609		4092613	4092616		30
								4092618	50
9	12.4	1200		4092619	4092620	4092621	4092623		40
		1350				4092622	4092624		40
12	16.6	1200				4092606			30





Intergroove[®]

Interior linings


Intergroove[®] is the perfect choice for creating a modern, floor to ceiling feature wall or a traditional dado wall design. This strong and durable internal wall lining is designed with a V-shaped groove, combining the classic look of traditional panelling with the modern benefits of fibre cement, including easy maintenance and lasting durability.

Features and benefits

- Easy to handle and built for long-lasting performance.
- Quick to install as it eliminates the need for taped and filled joints.
- Factory sealed panels aid paint application.
- Features a 2mm deep v groove.

Thickness mm	Weight kg/m ²	Width mm	Length mm	Product code	Pack size
7.5	10.4	1200	2700	4092659	50

Profile



Intergroove[®]





Innova on the inside


By leading the way in using fibre cement beyond traditional facades, Innova is redefining its role in residential and commercial interiors. Transforming industry perceptions, our range seamlessly extends from exterior to interior spaces with ‘Innova on the Inside’.

Innova fibre cement is ideal for interiors as an alternative and unique approach to feature walls inside the home or office space.

Innova's innovative products and ideals are changing perceptions of where fibre cement cladding can be used in residential and commercial environments — not just the exterior or as a lining board in wet areas.

Innova aims to quash misconceptions such as ‘fibre cement is typically for exterior facades’. Innova is committed to changing the perception that fibre cement can only be used externally and in wet areas, increasing understanding of how fibre cement can be used in interior settings industry-wide.

Providing aesthetics and versatility in design, Innova's broad range of fibre cement products are textured, smooth or ready for finishing on-site when other lining products need to be painted, wall-papered or tiled to achieve a visually pleasing finish.







Duralux®

Eaves and soffits

Eaves lining and soffits

Durasheet®

Eaves lining and soffits

Durasheet® is the ideal solution for gable ends, eaves lining, soffits, carports, and external ceilings. This versatile general-purpose sheet is compatible with both timber and steel-framed buildings, offering flexibility across various applications.

Available in two thicknesses, Durasheet® provides options for both residential and light commercial use. With a wide range of sizes, it accommodates both narrow and wide soffits, expanding your design possibilities.




Features and benefits

- 4.5mm thickness: used mainly in timber-framed residential buildings for soffit/eaves linings.
- 6.0mm thickness: recommended for light commercial applications, cladding features such as gable ends cyclonic wind zones and steel framed constructions.
- Can be hand nailed or screwed for convenience and efficiency.

Thickness mm	Weight kg/m ²	Width mm	Length and product code				Pack size
			1800mm	2400mm	2700mm	3000mm	
4.5	6.1	450		4092559			120
		600		4092560			120
		750		4092561			120
		900		4092562		4092565	60
		1200	4092557				60
				4092558	4092563	4092564	60/80
6	8.8	900		4092569		4092572	60
		1200	4092566	4092568	4092570	4092571	60



Accessories



PVC straight joint

PVC cap mould

Express joiner

Size mm	Product code	Size g	Product code	Size mm	Product code
4.5 × 2400	4092809	4.5 × 2400	4092856	8.5 × 50 × 3000	4095531
4.5 × 3000	4092810	6 × 2400	4092861		
6 × 2400	4092877	6 × 3000	4092865		
6 × 3000	4092879				



Duralux[®]

Eaves lining and soffits

Duralux[®] is a versatile general-purpose fibre cement building board designed for a wide range of demanding applications. Whether used for interior lining, domestic and commercial soffits, external ceilings, wet areas, or internally as a substrate for ceramic wall tiles, Duralux[®] delivers reliable performance in both residential and commercial settings.

With two available thicknesses, it's easy to apply to both timber and steel framing, making it a flawless choice for a variety of projects.

Features and benefits



- Correct installation and maintenance will ensure full water resistance for long-lasting performance.
- Can be easily decorated in a variety of finishes to suit your design needs.
- Ideal for expressed joint eaves and ceilings in residential, medium density and commercial applications.

Thickness mm	Weight kg/m ²	Width mm	Length and product code				Pack size
			2400mm	2700mm	3000mm	3600mm	
6	8.3	1200	4092635	4092637	4092638	4092639	60
9	12.4	1200	4092640	4092642	4092644		40





Accessories



PVC straight joint

PVC cap mould

Express joiner

Size mm	Product code	Size mm	Product code	Size mm	Product code
6 × 2400	4092877	6 × 2400	4092861	8.5 × 50 × 3000	4095531
6 × 3600	4092878	6 × 3000	4092865		
6 × 3000	4092879				



Durafloor®

Innova product brochure

Flooring and underlay

Flooring

Durafloor®

Flooring

Durafloor® provides one solution for substrate in interior wet areas such as bathrooms and laundries, as well as a range of exterior applications such as balconies and verandahs.

Its innovative tongue-and-groove joint eliminates the need for blocking, simplifying the installation process and speeding up the job. It is an excellent alternative to particle board or plywood.

Durafloor® is also perfect for use on balconies, verandahs, sun decks, and, when premium quality is essential, as a total floor solution.

Features and benefits

- Can be installed using traditional gun-nailing methods for efficiency.
- Compatible tongue and groove with particle board flooring.
- Fast installation, reducing install costs.
- Provides a solid, durable surface that feels more stable and secure underfoot compared to timber-based sheet flooring.

Thickness mm	Weight kg/m ²	Width mm	Length and product code			Pack size
			2250mm	2400mm	2700mm	
19	26.2	600	4092582		4092583	40
22	30.4	600		4092584		40





Compressed flooring

High-density compressed flooring is a premium substrate, primarily used in commercial applications for high-load areas. It is also ideal for interior floors in wet areas, as well as for upper storeys, transportable buildings, and exterior decks. Its durability and strength make it particularly well-suited for demanding environments.

Features and benefits

- Impact resistant and immune to termite attacks.
- Highly durable and has superior structural performance for high load applications.
- Suitable for both interior wet areas and external decking.
- Deemed non-combustible.

Thickness mm	Weight kg/m ²	Width mm	Length and product code				Pack size
			1800mm	2400mm	2700mm	3000mm	
15	24.8	1200	4092533	4092535	4092536	4092538	20
18	29.7	900		4092541		4092543	20
		1200	4092539	4092540		4092542	20
24	39.7	1200		4092544			15





Compressed
flooring



Ceramic tile
underlay

Flooring and underlay

Underlay

Ceramic tile underlay

Ceramic tile floor underlay is a specially formulated fibre cement sheet, designed as a stable substrate for slate and ceramic floor tiles. It offers a reliable base for tiling over both new and existing timber floors.

In dry areas, ceramic tile floor underlay creates an impervious, easily-cleaned surface, while in wet areas or locations prone to flooding or water splash, a waterproof membrane should be installed between the underlay and the tiles for added protection.

Features and benefits

- Engineered for optimal performance as a floor tile substrate.
- Excellent substrate for floor tiles, both slate and ceramic.
- Suitable for both dry and wet areas (with additional waterproofing as required).
- Can be applied to new or existing timber floors for added convenience.

Thickness mm	Weight kg/m ²	Width mm	Length mm	Product code	Pack size
6	8.4	1200	1800	4092792	60







Effects

Effects[®] trims

Effects[®] trims is a range of fibre cement trims designed to provide a polished finish around windows and doors, as well as internal and external corners. It can also be used as a decorative accent to create a distinctive feature in your design.

Effects[®] trims are available in a variety of sizes giving you ultimate design flexibility. Use one or mix and match to create a visually appealing design or surround. Innova Effects[®] fibre cement trims can be used with all Innova weatherboards and facades.

Features and benefits

- Add a sleek and stylish finish around windows.
- Creates a perfect line at internal and external corners.
- Can be used to create feature walls.
- 5 sizes available to suit a variety of installations.
- Maintains integrity and appearance longer than traditional timber trims.
- Complies with BAL-40 as required in AS 3959 — Construction of buildings in bushfire prone areas.

Thickness mm	Weight km/lm	Width mm	Product code	Length mm	Pack size
19	1.3	57	4094322	3000	1
	1.7	76	4094323		
	2.2	95	4094324		
38	2.3	50	4094325		
	4	88	4094326		



Effects[®] fascia

Effects[®] fascia is a specially formulated fibre cement board designed to provide long term durability and maintain an excellent finish for the life of the home.

Effects[®] fascia is the perfect choice to complement all Innova[®] cladding products, providing the aesthetics, performance and durability for any residential home design.

Features and benefits

- Designed to accommodate Durasheet[®] for a seamless transition.
- Gun nailable and easy to cut and handle.
- Pre-primed ready to paint.
- Provides a timber look without the problems associated with real timber and will not rot, swell, twist and is resistant to termites.
- Complies with BAL-29 as required in AS 3959 — Construction of buildings in bushfire prone areas.

Thickness mm	Weight kg/m ²	Width mm	Length mm	Pack size	Product code
14	18	175	4200	120	4093793



Effects[®] base trim

The Effects[®] base trim is specifically designed to provide the perfect finishing touch to slab edges, offering a sleek and contemporary aesthetic. Its design ensures a professional look while being ready for painting, making it an ideal choice for exteriors.

This innovative system includes a variety of components, enabling seamless completion of both internal and external corners. Additionally, the integrated joiner ensures a precise transition between trim lengths, delivering a neat appearance across the entire installation.

Features and benefits

- Add a sleek and stylish finish to the slab edge of your project.
- Maintains integrity and appearance longer than traditional timber trims.
- Quick and simple to install.
- Corrosion-resistant; coastal zone compatible.
- Provides a flashing function for any excess moisture, pushing water out and away from the internals.
- Set up level and the inbuilt 6mm ledge allows for holding panels during cladding installation.
- Ready for priming and paint of your choice.

Product compatibility

Duratex [®]	Stratum [®] 12mm
Durasheet [®] 6mm	Duragroove [®] 9mm
Duraplank [®]	Durascape [®] 9mm
Duragrid [®] 9mm	

May be used with Nuline[®] and Contour[®] but cladding will protrude past the face of Effects base trim.



Accessories

Product name	Size mm	Pack size	Product code	
Base trim	3950	1	4094245	
Straight joiner	57	1	4094246	
External corner	50 x 50	1	4094247	
Internal corner	50 x 50	1	4094248	



Nuline®
square 205

Fibre cement specialists. Built on change.

Adelaide
08 8480 1700

Brisbane
07 3548 8400

Melbourne
03 9492 1700

Perth
08 9311 5500

Sydney
02 8107 9500

Technical Helpline
1300 652 242

Follow us
Instagram @innovafibreceement

Facebook @innovafibreceement

LinkedIn /innova-fibre-cement

Warranty: Please refer to innovafibreceement.com.au for detailed warranty information.

Disclaimer: Innova regularly updates its literature; to ensure this document is current with the latest information, visit innovafibreceement.com.au



SCAN QR FOR
WEBSITE

INNOVA

by etex