

CEDRAL MOLINA SLATES

Product data sheet

Molina Natural Slates are sourced from Northern Spain.

Their coarse texture and blue grey colour will give any roof a natural, traditional look.

Molina come with a with a 50 year guarantee.



CI/SFB | | (4-) | NF9 | |

Technical data

Size of slate	600 x 300mm	500 x 250mm
Minimum pitch	25° (110mm headlap)	25° (110mm headlap)
Maximum pitch	90°	90°
Typical headlaps	100, 110mm	100, 110mm
Batten gauge	245-250mm	200-195mm
Slate thickness	5-6mm	5-6mm
Covering capacity	13.1 slates/m ² (100mm headlap) 13.4 slates/m ² (110mm headlap)	19.6 slates/m ² (100mm headlap) 19.9 slates/m ² (110mm headlap)
Average weight per slate	2.68kg (approx.)	1.75kg (approx.)
Typical quantity per crate	440 No.	610 No.
Battens required	4.00 (net lin.m/m ² at 100 mm headlap)	5.00 (net lin.m/m ² at 100 mm headlap)
Batten size recommended (fixed as per SR82: 2017)	50 x 25mm for rafter supports not exceeding 400mm centres 50 x 35mm for rafter supports not exceeding 600mm centres	50 x 25mm for rafter supports not exceeding 400mm centres 50 x 35mm for rafter supports not exceeding 600mm centres
Fixings	Slate nails (40 x 3.35mm) Slate hooks (2.5-3mm diameter)	Slate nails (40 x 3.35mm) Slate hooks (2.5-3mm diameter)
Accreditation	EN 12326-1	EN 12326-1
Thermal cycle resistance	Class T1	Class T1
Water absorption	Class W1	Class W1
Sulphur dioxide exposure resistance	Class S1	Class S1

Cedral is independently certified as meeting requirements of ISO 9001 (Quality), ISO 14001 (Environment), OHSAS 18001 (Safety) and are rated "Excellent" in the BES 6001 Standard for responsible sourcing.

For further information visit cedral.ie, call +353 (0)59 863 1316 or email our technical support department on info.ireland@cedral.world

more at cedral.ie

Tel: +353 (0) 59 863 1316 Email: info.ireland@cedral.world
 Etex Ireland Ltd, Kilkenny Road, Athy, Kildare, Ireland, R14VN84