

Product description

The EQUITONE EPDM tape is a non-reinforced EPDM waterproofing. The product is black and has a textured surface on both sides. It is used to protect the battens against permanent moisture penetration when fastening EQUITONE façade panels. Store in the original packaging in a cool, dry place. There are no restrictions on storage. Before installation, read the planning & application EQUITONE façade panels on timber support frame.



1. Technical characteristics

Width	70 mm	110 mm	130 mm
Weight	90.3 g/m	141.9 g/m	167.7 g/m
Article Nr.	4010489	4010490	4030354
Thickness	1 mm		
Roll length	20 m		
Colour	Black		

2. Technical data

Reaction to fire	EN 13501-1	Class E
Watertightness (2 kPa)	EN 1928 B	Passed
Tear resistance (Nail shank)	EN 12310-1	160 N
Elongation at rupture	EN 12311-2 (B)	300 %
Tensile strength	EN 12311-2 (B)	6 MPa
Durability (aging - 2 kPa)	EN 1296 / EN 1928	Passed
Hazardous Substances	Construction Products Regulation	None

Disclaimer

The information in this document is correct at time issuing. However, due to our committed program of continuous material and system development we reserve the right to amend or alter the information contained therein without prior notice. Please visit www.equitone.com to ensure you have the most current version. All figures contained in this document are illustrations and should not be used as construction drawings. This information is supplied in good faith and no liability can be accepted for any loss or damage resulting from its use. This document is protected by international copyright laws. Reproduction and distribution in whole or in part without prior written permission is strictly prohibited. EQUITONE and logos are trademarks of Etex NV or an affiliate thereof. Any use without authorisation is strictly prohibited and may violate trademark laws.