November 2026 | Data Sheet | ursa-uk.co.uk

URSA WALLTEC BLACK 32

Typical applications:

New bulid and refurbishment rainscreen cladding.



Description.

URSA WALLTEC BLACK 32 is a non-combustible British Board of Agrément (BBA) approved glass mineral wool insulation slab. It is treated with a silicone-based water repellent and features a black glass fibre tissue facing on one side which is applied during the manufacturing process.

The black tissue facing provides an aesthetic solution, allowing the product to be used behind open joint cladding without being visible.

Non-combustible

Thermal Insulation

up to 73% Recycled Glass Content

CCPi ASSESSED PRODUCT INFORMATION 005800174/0727 URSA Rainscreen Cladding Insulation

Application.

URSA WALLTEC BLACK 32 is used as thermal and acoustic insulation on timber frame, steel frame or masonry backgrounds with ventilated rainscreen façade systems or a masonry outer leaf. In ventilated façade systems it can be used on buildings of any height; with a masonry outer leaf buildings above 25m are subject to additional design guidance (see BBA Certificate). It is suitable for both new and existing domestic and non-domestic buildings. Additionally, it can be used as soffit insulation.

Please refer to the Design & Installation Guides for more information.

Performance.

Thermal Conductivity:
Declared thermal conductivity (lambda (λ) value) of 0.032 W/mK.

Density:
Manufactured at a nominal density of 32 kg/m³.

Fire Classification:
Deemed non-combustible with a fire classification of Euroclass A1 (the highest possible rating) when tested to EN 13501-1:2018 Reaction to Fire.

Technical Characteristics.

Product Specification.

Thickness (mm)	Length (mm)	Width (mm)	Slabs per pack	Pack Area (m^2)	Packs per pallet	Pallet Area (m^2)	Thermal Conductivity (W/mK)	Thermal Resistance (m^2K/W)	Product Code
40	1350	600	15	12.15	16	194.40	0.032	1.25	331247
50	1350	600	11	8.91	20	178.20	0.032	1.55	331879
60	1350	600	9	7.29	20	145.80	0.032	1.85	332479
80	1350	600	7	5.67	20	113.40	0.032	2.50	332070
100	1350	600	5	4.05	20	81.00	0.032	3.10	332071
120	1350	600	5	4.86	16	77.76	0.032	3.75	331821
130	1350	600	5	4.05	16	64.80	0.032	4.05	331880
140	1350	600	5	4.05	16	64.80	0.032	4.35	332072
150	1350	600	4	3.24	16	51.84	0.032	4.65	332892
160	1350	600	4	3.24	16	51.84	0.032	5.00	332073
180	1350	600	3	2.43	20	48.60	0.032	5.60	332480
200	1350	600	3	2.43	16	38.88	0.032	6.25	332372
220	1350	600	3	2.43	16	38.88	0.032	6.85	332481
240	1350	600	3	2.43	16	38.88	0.032	7.50	331751

Please note that all dimensions are nominal.

Additional Information.

CCPI (Code for Construction Products Information)

Holds CCPI Assessment Mark.
Certificate number: 005800174/0727.

Vapour Resistivity.

The product has a nominal vapour resistivity of 5 MNs/gm.

Durability.

URSA has undertaken both in-house and independent testing to assess the durability of URSA WALLTEC BLACK 32 against wind driven rain and high winds. This involved leaving the slabs exposed on a test wall for several months and testing to EN 12865:2001. This test assesses external wall systems resistance to driving rain under pulsating air pressure; it is intended for the complete wall system so is very onerous onto the insulation alone. Wind speeds up to 31 m/s (70mph) did not damage the slabs and rain at a pressure of 1200 Pa gave surface wetting only and did not result in water penetration through the slabs.

Environmental Credentials.

- EN 13162:2012+A1:2015 Thermal insulation products for buildings – Factory made mineral wool (MW) products.
- ISO 14001:2015+A1:2024 - Environmental Management Systems (EMS) certified. Certificate number: BQA_EMS_C_2016673.
- Contains no ozone-depleting substances or greenhouse gases.
- Manufactured from up to 73% recycled glass.
- Environmental Product Declarations (EPDs) for our products, detailing their overall environmental performance, are published and accessible on our website.

Standards and Approvals.

Manufactured in accordance with:

- EN 13162:2012+A1:2015 Thermal insulation products for buildings – Factory made mineral wool (MW) products.
- EN 13172: 2012 Thermal insulation products - Evaluation of conformity.
- ISO 9001:2015 - Quality Management Systems (QMS). Certificate number: 01 100 1300949.

Certification.

- CE Marked to EN 13162:2012+A1:2015. Certificate number: 1163-CPR-0041.
- British Board of Agrément (BBA) certified for use behind rainscreen and masonry cladding. Certificate number: 20/5832.

EUCEB (European Certification Board of Mineral Wool Products)

All URSA glass mineral wool products are made of non-classified fibres and are certified by EUCEB. EUCEB is a voluntary initiative by the mineral wool industry. It is an independent certification authority that guarantees that products are made of fibres which comply with the exoneration criteria for carcinogenicity (Note Q) of the Regulation (EC) 1272/2008.

Certificate number: BEUC-511-46-376-46.

Handling & Storage.

The product must be stored and handled in a manner that ensures it remains clean and undamaged.

It is supplied compression-packed in polythene, which provides short-term protection only. For long-term protection, store the product indoors or under a waterproof covering, raised off the ground, to prevent weather-related damage. The product must not be left permanently exposed to the elements.

All URSA products are non-hygroscopic, will not rot, degrade, or sustain vermin and will not encourage the growth of mould, bacteria, or fungi.

URSA TERRA.

Developed in 2009, URSA TERRA showcases the latest in glass mineral wool technology. Our distinctive production methods and product formulation define the character of our extensive insulation product range.

Etex UK Insulation Limited. Thistle Industrial Estate, Kerse Road, Stirling, Scotland FK7 7QQ **ursa-uk.co.uk**

Technical: T. **0808 1645 134** | E. **technicalursa.uk@etexgroup.com** | Customer Services: T. **01786 451170** | E. **customerservice.stirling@etexgroup.com**

All rights are reserved, including those of photomechanical reproduction and storage in electronic media. Commercial use of the processes and work activities presented in this document is not permitted. Extreme caution was observed when putting together the information, texts, and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of errors pointed out. Please check this is the current version by visiting the URSA website. For archived versions please contact the Technical Services Team.

REF: 51040

USWTB07
November 2026