November 2026 | Data Sheet | ursa-uk.co.uk

URSA HOMETEC ROLL 32

Typical applications:

Twin skin profiled metal clad systems.





Description.

URSA HOMETEC ROLL 32 is a non-combustible glass mineral wool insulation roll. The roll is supplied 1200mm wide.

Non-combustible

Thermal Insulation

Recycled Glass Content

CCPI ASSESSED PRODUCT INFORMATION 005800185/1027 URSA Building Insulation

Application.

URSA HOMETEC ROLL 32 is designed to provide thermal and acoustic insulation in the walls and roofs of twin skin profiled metal clad systems and portable & modular buildings.

The product can also be used as thermal and acoustic insulation various applications, including timber frame walls, roofs, and floors.

Performance.

Thermal Conductivity:
Declared thermal conductivity (lambda (λ) value) of 0.032 W/mK.

Density:
Manufactured at a nominal density of 32 kg/m³.

Fire Classification:
Deemed non-combustible with a fire classification of Euroclass A1 (the highest possible rating) when tested to EN 13501-1:2018 Reaction to Fire.

Technical Characteristics.

Product Specification.

Thickness (mm)	Length (mm)	Width (mm)	Pack Area (m^2)	Packs per pallet	Pallet Area (m^2)	Thermal Conductivity (W/mK)	Thermal Resistance (m^2K/W)	Product Code
60	5400	1200	6.48	18	116.64	0.032	1.85	332913
80	5400	1200	6.48	18	116.64	0.032	2.50	332928
101	5000	1200	6.00	18	108.00	0.032	3.15	332546
120	4500	1200	5.40	18	97.20	0.032	3.75	331822
140	3700	1200	4.44	18	79.92	0.032	4.35	331823
160	3300	1200	3.96	18	71.28	0.032	5.00	331824
180	3000	1200	3.60	18	64.80	0.032	5.60	331875
200	2600	1200	3.12	18	56.16	0.032	6.25	333154
220	2500	1200	3.00	18	54.00	0.032	6.85	332539
240	2400	1200	2.88	18	51.84	0.032	7.50	332122

Please note that all dimensions are nominal.

Additional Information.

CCPI (Code for Construction Products Information).

Holds CCPI Assessment Mark.
Certificate number: 005800185/1027.

Vapour Resistivity.

The product has a nominal vapour resistivity of 5 MNs/gm.

Environmental Credentials.

- The primary packaging on our products (rolls and slabs) and pallets (the shrink hood) are wrapped in low-density polyethylene (LDPE4) plastic, which contains a minimum 30% recycled material and is fully recyclable. The secondary packaging on our products (grouping rolls and slabs into modules of 3-6 packs) is low-density polyethylene (LDPE4) virgin plastic. Before recycling, please consult your local authority for guidance.
- ISO 14001:2015+A1:2024 - Environmental Management Systems (EMS) certified. Certificate number: BQA_EMS_C_2016673.
- Contains no ozone-depleting substances or greenhouse gases.
- Manufactured from up to 73% recycled glass.
- Environmental Product Declarations (EPDs) for our products, detailing their overall environmental performance, are published and accessible on our website.

Standards and Approvals.

Manufactured in accordance with:

- EN 13162:2012+A1:2015 Thermal insulation products for buildings – Factory made mineral wool (MW) products.
- EN 13172: 2012 Thermal insulation products - Evaluation of conformity.
- ISO 9001:2015 - Quality Management Systems (QMS). Certificate number: 01 100 1300949.

Certification.

- CE marked to EN 13162:2012+A1:2015. Certificate number: 1163-CPR-0051.

EUCEB (European Certification Board of Mineral Wool Products).

All URSA glass mineral wool products are made of non-classified fibres and are certified by EUCEB. EUCEB is a voluntary initiative by the mineral wool industry. It is an independent certification authority that guarantees that products are made of fibres which comply with the exoneration criteria for carcinogenicity (Note Q) of the Regulation (EC) 1272/2008.
Certificate number: BEUC-511-46-376-46.

Handling & Storage.

The product must be stored and handled in a manner that ensures it remains clean and undamaged. It is supplied compression-packed in polythene, which provides short-term protection only. For long-term protection, store the product indoors or under a waterproof covering, raised off the ground, to prevent weather-related damage.

During construction, all exposed areas of the product must be covered at the end of each working day and during adverse weather conditions, including rain, wind, or snow. Use polythene sheeting or an equivalent protective cover to prevent water saturation. The product must not be left permanently exposed to the elements.

All URSA products are non-hygroscopic, will not rot, degrade, or sustain vermin and will not encourage the growth of mould, bacteria, or fungi.

URSA TERRA.

Developed in 2009, URSA TERRA showcases the latest in glass mineral wool technology. Our distinctive production methods and product formulation define the character of our extensive insulation product range.

URSA by etex | CE | EUCEB | NBS Source PARTNER

Etex UK Insulation Limited. Thistle Industrial Estate, Kerse Road, Stirling, Scotland FK7 7QQ **ursa-uk.co.uk**

Technical: T. **0808 1645 134** | E. **technicalursa.uk@etexgroup.com** | Customer Services: T. **01786 451170** | E. **customerservice.stirling@etexgroup.com**

All rights are reserved, including those of photomechanical reproduction and storage in electronic media. Commercial use of the processes and work activities presented in this document is not permitted. Extreme caution was observed when putting together the information, texts, and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of errors pointed out. Please check this is the current version by visiting the URSA website. For archived versions please contact the Technical Services Team.

REF: 51040

USHT3205
November 2026