

URSA DF 39-Ah

MW-EN-13162-T2-MU1-AF5



Lagani filc od mineralne staklene vune u rolni, kaširan ALU folijom, komprimovan u odnosu 1:5.

Područje upotrebe:

- ✓ Toplotna i zvučna izolacija:
 - klima kanala,
 - cevovoda,
 - rezervoara i
 - drugih konstrukcija u tehnici, industriji i brodogradnji.

Debljina [mm]	30	50	60	80	100	120	140	150	160	180	200	220	240
Širina [mm]	1200	1200	1200	1200	1200	1200	1200	1200	1200	1200	1200	1200	1200
Dužina [mm]	18000	15000	11500	9400	7500	6200	5400	5000	4700	4200	3700	3400	3100
Toplotni otpor R_0 [m^2K/W]	0,77	1,25	1,50	2,05	2,55	3,05	3,55	3,80	4,10	4,60	5,10	5,60	6,15

TEHNIČKE INFORMACIJE

	20 °C	30 °C	40 °C	
• Toplotna provodljivost λ_0	0,037 W/mK	0,038 W/mK	0,040 W/mK	SRPS EN 12667
• Klasa reakcije na vatru	A1			SRPS EN 13501-1
• Linearni otpor strujanju vazduha r	> 5 kPa s/m ²			
• Granična temperatura upotrebe	200°C			



Proizvod je sertifikovan u skladu s EN 13162.

EG certifikat o usaglašenosti broj.: 0672 – CPR – 0319.

MW – skraćena oznaka za mineralnu vunu

EN 13162 – broj evropskog standarda

Ti – tolerancija debljine

TRi – delaminaciona čvrstoća

WL(P) - upijanje vode metodom dugotrajnog uranjanja

MU1 - difuzija vodene pare

SDi – nazivna vrednost dinamičke krutosti

CPI – stišljivost

AFi - linearni otpor strujanju vazduha

