


# Superglass Slab 32.

September 2025 | Data Sheet



## Description.

Superglass Slab 32 is a non-combustible glass mineral wool insulation slab. The flexible slab is supplied at 600mm width to allow friction fitting between common stud/joist spacings, minimising gaps at joints and reducing on-site cutting & waste.

## Application.

Superglass Slab 32 is designed to provide both thermal and acoustic insulation for various applications, including:

- Light steel framing systems (between studs only)
- Internal walls and floors
- Separating walls and floors
- Timber and metal stud partitions
- Timber frame roofs and floors

## Performance.

### Thermal Conductivity:

Declared thermal conductivity (lambda ( $\lambda$ ) value) of 0.032W/mK.

### Fire Classification:

Deemed non-combustible with a fire classification of Euroclass A1 (the highest possible rating) when tested to BS EN 13501-1:2018  
Reaction to Fire.



**Typical applications:**  
Multi-Application use.



Acoustic  
Insulation



Thermal  
Insulation



Non-  
combustible



Recycled  
Glass Content

intelligent environments  
**Superglass**  
by etex

[superglass.co.uk](http://superglass.co.uk)

# Superglass Slab 32.

## Technical Characteristics.

### Product Specification.

Thickness (mm)	Length (mm)	Width (mm)	Slabs per pack	Pack Area (m <sup>2</sup> )	Packs per pallet	Thermal Conductivity (W/mK)	Thermal Resistance (m <sup>2</sup> K/W)	Product Code
40	1200	600	12	8.640	20	0.032	1.25	2145034
80	1200	600	6	4.320	16	0.032	2.50	2144383
90	1200	600	6	4.320	16	0.032	2.80	2144382
100	1200	600	6	4.320	16	0.032	3.10	2144381
150	1200	600	4	2.880	16	0.032	4.65	2144375

Please note that all dimensions are nominal.

### Additional Information.

#### Vapour Resistivity.

The product has a nominal vapour resistivity of 5 MNs/gm.

#### Environmental Credentials.

- Our products and their pallets are wrapped in low-density polyethylene (LDPE4) plastic, which contains a minimum 30% recycled material and is fully recyclable. Before recycling, please consult your local authority for guidance.
- ISO 14001:2015 – Environmental Management Systems (EMS) certified. Certificate number: EMS 646508.
- Contains no ozone-depleting substances or greenhouse gases.
- Made from up to 84% recycled glass.
- Generic BRE Green Guide Rating of A+.

For more information, please refer to the Environmental Product Declaration (EPD).

#### Standards and Approvals.

Manufactured in accordance with:

- BS EN 13162:2012+A1:2015 Thermal insulation products for buildings - Factory made mineral wool (MW) products.
- BS EN 13172: 2012 Thermal insulation products - Evaluation of conformity.
- ISO 9001:2015 – Quality Management Systems (QMS). Certificate number: FM 02264.

#### Certifications.

- UKCA certified to BS EN 13162:2012+A1:2015. Certificate number: 0086 CPR 469699.
- CE marked to EN 13162:2012+A1:2015. Certificate number: 0751-CPR-399.0-01.

A copy of the product Declaration of Performance (DoP) can be downloaded from the Superglass website.

#### EUCEB (European Certification Board of Mineral Wool Products).

All Superglass glass mineral wool products are made of non-classified fibres and are certified by EUCEB. EUCEB is a voluntary initiative by the mineral wool industry. It is an independent certification authority that guarantees that products are made of fibres which comply with the exoneration criteria for carcinogenicity (Note Q) of the Regulation (EC) 1272/2008. Certificate number: BEUC-511-27949-491-14462.

#### Handling & Storage.

The product should be stored properly and handled in such a way as to ensure that the product remains clean and undamaged.

The product is supplied compression packed in polythene to provide short term protection only. For long term protection, the product must be stored indoors, or under a waterproof covering and off the ground to protect from weather damage. The product should not be left permanently exposed to the elements.

All Superglass products are non-hygroscopic, will not rot, degrade, or sustain vermin and will not encourage the growth of mould, bacteria, or fungi.



Etex UK Insulation Limited | Thistle Industrial Estate | Kerse Road | Stirling | FK7 7QQ | UK

SS3204  
September 2025

#### Technical

Hotline: 0808 1645 134

Email: [technical.stirling@etexgroup.com](mailto:technical.stirling@etexgroup.com)

#### Customer Services

Tel: 01786 451170

Email: [customerservice.stirling@etexgroup.com](mailto:customerservice.stirling@etexgroup.com)

#### Social

[superglass\\_uk](#)

[superglassuk/](#)

[superglassinsulationuk](#)